Amendments to the Claims:

Please cancel claims 4, 7 and 22 which stand withdrawn from consideration as being directed to a non-elected invention, without prejudice or disclaimer of the subject matter thereof and without prejudice to the right to file a divisional application directed thereto.

Please cancel claims 3, 6 and 21 without prejudice or disclaimer of the subject matter thereof, amend claim 1 to incorporate the features of claim 21 therein, amend claim 5 to incorporate the features of claim 6 therein and amend claim 8 as follows.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) A liquid crystal display device comprising a plurality of video signal lines and a plurality of pixel electrodes which are arranged in a matrix array and to which video signals are supplied from the video signal lines on one of a pair of substrates which sandwich a liquid crystal layer therebetween, wherein:

one substrate includes a plurality of conductive layers which are provided at positions where portions thereof overlap the video signal lines and are separated therefrom by way of an insulation film, and

the respective conductive layers are electrically connected to respective video signal lines

wherein each conductive layer is electrically connected to the video signal line at one point by way of a contact hole formed in the insulation film.

2. (original) A liquid crystal display device according to claim 1, wherein a backlight is provided at a side of one substrate opposite to the liquid crystal layer, and the conductive layer prevents light from the backlight from leaking through a gap defined between two neighboring pixel electrodes.

Claim 3 (canceled)

Claim 4 (canceled)

5. (currently amended) A liquid crystal display device comprising a plurality of scanning signal lines, a plurality of video signal lines which cross the plurality of scanning signal lines, and a plurality of pixels which are arranged in a matrix array on one of a pair of substrates which sandwich a liquid crystal layer therebetween, wherein:

each pixel in the plurality of pixels includes a switching element driven by the scanning signal line and a pixel electrode to which video signals are supplied from the video signal line through the switching element;

one substrate includes opaque conductive layers at positions where portions thereof overlap the video signal lines and are separated therefrom by way of an insulation film, such that the opaque conductive layers are arranged closer to one substrate side than the video signal lines; and

each opaque conductive layer has a portion which has a width greater than the width of the video signal line, each opaque conductive layer is partially overlapped with respect to both of adiacent_adjacent_pixel electrodes of two

neighboring pixels with the video signal line being arranged therebetween, and each opaque conductive layer is electrically connected to a video signal line;

wherein each opaque conductive layer is electrically connected to a video signal line at one point by way of a contact hole formed in the insulation film.

Claim 6 (canceled)

Claim 7 (canceled)

- 8. (currently amended) A liquid crystal display device according to claim 5, wherein the video signal line and the opaque conductive layer are electrically connected to each other via a contact hole formed in the insulation film, and the video signal line has a larger-width at a portion thereof which is larger than a width of the corresponding to the contact hole than a width at other portions-thereof.
- 9. (previously presented) A liquid crystal display device according to claim 5, wherein the video signal line has at least a portion which has a width equal to or smaller than a gap between adjacent pixel electrodes of two neighboring pixels, with the video signal line being arranged therebetween.
- 10. (previously presented) A liquid crystal display device according to claim 5, wherein the area of a portion where the opaque conductive layer and the pixel electrode overlap each other is larger than the area of a portion where the video signal line and the pixel electrode overlap.

- 11. (original) A liquid crystal display device according to claim 5, wherein the opaque conductive layer is formed of the same material as the scanning signal line.
- 12. (original) A liquid crystal display device according to claim 5, wherein the liquid crystal display device includes a plurality of capacitance lines for forming storage capacitances in the respective pixels and the opaque conductive layers are formed of the same material as the capacitance lines.
- 13. (original) A liquid crystal display device according to claim 5, wherein the opaque conductive layers are formed in independent patterns corresponding to a gap between two neighboring pixels.
- 14. (original) A liquid crystal display device according to claim 5, wherein the pixel electrode is a transparent electrode.
- 15. (original) A liquid crystal display device according to claim 5, wherein the pixel electrode is a reflective electrode.
- 16. (previously presented) A liquid crystal display device according to claim 5, wherein the pixel electrode is a reflective electrode and each pixel includes a second pixel electrode which is formed as a transparent electrode and to which the video signals are applied.

17. (previously presented) A liquid crystal display device according to claim 16, wherein the opaque conductive layer is formed at a position where the opaque

conductive layer does not overlap the second pixel electrode.

18. (previously presented) A liquid crystal display device according to claim 16,

wherein a step portion is formed between the transparent electrode in a light

transmitting region and the reflective electrode in a light reflective region, and the

thickness of the liquid crystal layer in the light transmitting region is greater than the

thickness of the liquid crystal layer in the light reflective region.

19. (previously presented) A liquid crystal display device according to claim 5,

wherein the distance from the opaque conductive layer to the pixel electrode as

measured in the vertical direction with respect to the substrate is greater than the

distance from the video signal line to the pixel electrode as measured in the vertical

direction with respect to the substrate.

20. (original) A liquid crystal display device according to claim 5, wherein the liquid

crystal display device includes a backlight.

Claim 21 (canceled)

Claim 22 (canceled)

6